

TP 17 650



| Technical data | | |
|--------------------|--|---|
| Type | TP 17 650 | |
| Control sensor | Internal | |
| Dry block | | |
| Temperature range* | RT...650 °C | RT...1202 °F |
| Accuracy | ±0.8 °C | ±1.44 °F |
| Stability | ±0.1 °C | ±0.18 °F |
| Measurement zone | 110...150 mm | 4.3...5.91 in. |
| Block dimensions | | |
| ↑↑ Diameter | Ø 28 mm | Ø 1.10 in. |
| ↑↑ Depth | 150 mm | 5.91 in. |
| Display unit | | |
| Display | 2-line, 4-digit display Red / green, unit °C / °F | |
| Display range | 0...650 °C | 32...1202 °F |
| Resolution | 0.1 °C | 0.1 °C between RT...999.9 °F, else 1 °F |
| General data | | |
| Dimensions | | |
| ↑↑ Width | 150 mm | 5.91 in. |
| ↑↑ Height | 330 + 70 mm | 12.99 + 2.76 in. |
| ↑↑ Depth | 270 mm | 10.63 in. |
| Weight | Approx. 7.5 kg | Approx. 16.53 lbs. |
| Power supply | 230 / 240 VAC, 50 / 60 Hz, optional 100...115 VAC, 50 / 60 Hz optional 100...240 VAC, 50 / 60 Hz | |
| Power consumption | Approx. 1000 W | |

* At an ambient temperature of 20 °C / 68 °F

Scope of delivery

- Test certificate
- Mains cable
- Insert exchange tool
- Operating manual

Accessories

- Transport case
- Service transport bag
- Adapter sleeve